

TX standard pocket transmitter

Technical data



TX standard pocket transmitter

Frequency range	470 – 960MHz (specify at time of order)
Switching bandwidth	Up to 24MHz in 25kHz steps
Number of frequency tables	1
Number of factory pre-set frequencies	32
Number of user selectable frequencies	32 (selectable in 25kHz steps)
Manual tune mode	Yes - in 25kHz steps (can be saved to memory)
Modulation mode	Wideband FM
Frequency stability	±0.002%
Audio frequency response	80 – 18kHz
Signal-to-noise ratio	>100dB (±45kHz deviation)
Total harmonic distortion	<0.3% typ.
Output power	50mW nominal
Audio gain control	0-35dB (in 10 steps) mic and line inputs
Input connector	3.5mm stereo screw-locking
Display	OLED blue, 128x32 pixels
Control	3 position navigation switch
Battery type	1 x 1.5V alkaline LR6 AA size
Battery life	6 to 8 hours depending on battery type Audio recommends using NiMh type batteries
Operating temperature range	-20° C to +55° C
Weight	118 grams (without batteries)
Dimensions	63mm (W) x 82mm (H) x 20mm (D)
Accessories	Flexible clear antennae (straight) Input cable 3.5mm to XLR female connector ALM lavalier microphone Neoprene pouch

For further information contact Audio Ltd or your local distributor

www.audioltd.com

As we are always seeking to improve our products, specifications shown are subject to change.

TX0313-cwp